



PROVIDE SHADE TREES AT SEATING AREA
 BENCHES AND TRASH RECEPTACLE
 ASPHALT PATHWAY MIN. 4000 WIDTH AT BENCH LOCATIONS

TYPICAL PLAY STRUCTURE, REFER TO SPECIFICATIONS; ALL STEEL CONSTRUCTION, COMPONENTS, INCLUDING PLATFORMS, SLIDES, STEPS, CLIMBING APPARATUS, TO THE APPROVAL OF THE PLANNING, DESIGN AND DEVELOPMENT DEPARTMENT.

EDGING CURB, REFER TO SPECIFICATIONS SHOWN ON DETAILS L311-L313

SLIDES TO FACE NORTH

1800 MIN. SAFETY ZONE AROUND PLAY EQUIPMENT

20000

SETBACK TO PROPERTY LINES, FACILITIES, AND STREET CURBS. IF LESS, PROVIDE 1200 MM HT. DECORATIVE FENCES LOCATED AS DETERMINED ON A CASE BY CASE BASE.

2 BABY OR 1 BABY AND 1 ACCESSIBLE SEATS (8') TYPICAL

PLAY AREA SURFACE MATERIAL AND DEPTH AS SPECIFIED

4 ADULT (10') SEATS TYPICAL

ALL PLAY GROUNDS TO HAVE SUBSURFACE DRAINAGE

100 DIA. NON PERFORATED RIGID PVC DRAIN PIPE TO CATCHBASIN @ 2% SLOPE

NOTES:

1. PLAY AREA AND STRUCTURE SHOWN DO NOT REPRESENT A STANDARD. SCHEMATIC REPRESENTS ONLY TYPICAL MINIMUM SAFETY ZONES, DRAINAGE PATTERNS, AND MINIMUM SETBACKS.
2. PLAY STRUCTURE COMPONENTS, AND MINIMUM ZONES TO COMPLY WITH THE CURRENT CSA STANDARDS SUBGRADE TO BE AT 2% SLOPE.
3. SUBGRADE TO BE AT 2% SLOPE.
4. EXISTING AND NEW TREES SHALL BE UTILIZED TO PROVIDE MAXIMUM SHADE TO SEATING AND PLAY AREA.
5. LAY OUT SHALL ALLOW FOR ALTERNATE CURB OR EDGE DESIGN (SEE DETAILS L311-L313).
6. ALL MEASUREMENTS ARE IN MILLIMETRES UNLESS STATED OTHERWISE.